## Copps Industries, Incorporated 10600 N. Industrial Drive Mequon, WI 53092-4473 Telephone: (262) 238-1700

			Section	on 1 - Materia	l Identific	ation	
Product Name:		A-501GY					
Product Type:		Epoxy Resi	n Compour	nd			
Manufacturer:	Copps Industries, Incorporated						
		10600 N. I					
		Mequon, W		473			
Telephone Number:		(262) 238-	700				
<b>Emergency Number (s):</b>		(800) 255-3	3924	24 hrs.		(Continental	U.S.)
		(813) 248-0	)585	24 hrs.		(Outside Con	tinental U.S
<b>Revision Notes:</b>		Annual Up					
			Sectio	on 2 - Hazardo	ous Ingred		
<u># wt %</u>		Number		nemical Name			
1. >1 %	14808	3-60-7	Sil	ica, Crystalline	e, Quartz		
OSHA & ACGIH EXPOS	URE LIN	1ITS					
	Т	WA	ST	TEL	CE	ILING	
	ppm	mg/m3	ppm	mg/m3	ppm	mg/m3	
1. OSHA	N/E	15 (dust)	N/E	N/E	N/E	N/E	_
ACGIH	N/E	10 (dust)	N/E	N/E	N/E	N/E	
N/E = Not Established							
				ection 3 - Heal			

HMIS HEALTH RATING	2	FLAMM	IABILITY: 1	ŀ	REACTIVITY: 0
HMIS HEALTH RATING			ABILITY: 1		**************************************
					*****
EMERGENCY OVERVIEW					

A dark grey liquid with a strong "sweet" odor. Causes eye and skin irritation. Can burn in fire, releasing possible hazardous vapors, gases and

fumes. Do not torch or weld on cured epoxy. Hazardous fumes and vapors may be released.

Routes of Exposure: Eye Contact, Skin Contact, Ingestion.

Health Hazards: May cause eye irritation. May cause skin sensitization. Moderate skin irritant.

Target Organs: Eyes, Skin.

Signs and Symptoms of Exposure (Acute Effects): Contact with skin or eyes causes irritation, redness and discomfort.

Signs and Symptoms of Exposure (Possible Longer Term Effects): Repeated and/or prolonged exposure may cause allergic reaction/

sensitization. Repeated and/or prolonged exposure may result in adverse eye effects (such as conjunctivitis or corneal damage), adverse skin effects (such as rash, irritation or corrosion).

Medical Conditions Generally Aggravated by Exposure: Eye disease, skin disorders and allergies.

Carcinogens under OSHA, ACGIH, NTP, IARC, other: This product contains no carcinogens in concentrations of 0.1 percent or greater.

Copps Industries, Incorporated
Mequon, WI 53092-4473
Telephone: (262) 238-1700

No data

No data

Upper Explosion Limit (UEL):

#### Section 4 - First Aid

.....

Eye Contact: Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention.

Skin Contact: Remove contaminated clothing/shoes and wipe excess from skin. Flush skin with water. Follow by washing with soap and water. If irritation occurs, seek medical attention. If contact with hot product occurs, immediately flush with cool water for 15 minutes. Carefully remove clothing; if clothing is stuck to a burn area do not pull it off, but cut around it. Cover burn area with a clean material. Get medical attention immediately.

Inhalation: Remove victim to fresh air and provide oxygen. If breathing is difficult, seek medical attention.

Ingestion: If swallowed, call physician immediately. Induce vomiting only as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

## Section 5 - Fire and Explosion Data

\_\_\_\_\_ **Flash Point (closed cup):**  $> 200 \text{ }^{\circ}\text{F}$ 

Auto Ignition Temperature: No data

\_\_\_\_\_

Lower Explosion Limit (LEL): Fire Hazard Classification (OSHA/NFPA): This product is not considered flammable nor combustible, but will burn if involved in a fire.

Extinguishing Media: Foam, Carbon Dioxide (CO2), or dry chemical.

Special Fire Fighting Procedures: Keep personnel removed from area and upwind of fire. Wear full fire-fighting turn-out gear (full bunker gear) and respiratory protection (SCBA). Cool fire exposed containers with water spray.

Unusual Fire and Explosion Hazards: Hazardous combustion products may be present. Combustion may form aldehydes, nitrous oxides, carbon monoxide (CO), and carbon dioxide (CO2).

Section 6 - Accidental Release Measures

Containment Techniques (Removal of ignition sources, diking, etc.) Stop the leak, if possible. Shut off or remove all ignition sources. Construct a dike to prevent spreading.

\_\_\_\_\_

Clean-Up Procedures: Spread absorbent material over area. Wipe or scrape up material. Dispose of material in accordance with local, state and federal regulations. Wash area with soap and water. Prevent washings from entering sewers or waterways.

Other Emergency Advice: Wear protective clothing, boots, gloves, respirator, and eye protection. 

#### Section 7 - Handling and Storage

\_\_\_\_\_ Storage: Store in a cool (60-80 °F), dry, ventilated place. Crystallization may occur if storage temperature drops below 55 °F for a prolonged period of time. Store in closed containers.

Handling: Avoid contact with skin, eyes, or clothing. When handling, do not eat, drink, or smoke.

Other Precautions: Wash thoroughly after handling. Remove contaminated clothing and gear. Decontaminate. Destroy leather or any articles which can not be decontaminated.

#### Section 8 - Personal Protection/Exposure Controls

------Eye Protection: Chemical safety goggles recommended. Contact lenses should not be worn while using this product.

Hand Protection: Chemical resistant gloves recommended, such as neoprene or nitrite rubber.

Respiratory Protection: Not necessary under most operating conditions. NIOSH approved organic vapor respirator should be used in confined areas, or when conditions cause high vapor concentrations. If the percent oxygen is below normal then use self-contained breathing apparatus. Protective Clothing: Clean, body covering clothing should be utilized.

Work and Hygienic Practices: Eye wash stations and safety showers should be easily accessible.

## Section 9 - Typical Physical and Chemical Properties

Physical Form:	Liquid	Vapor Density:	Heavier than air
Color:	Dark Grey	<b>Boiling Point:</b>	> 200 °F
Odor:	Sweet	Melting Point:	Not Applicable
pH:	No Data	Solubility in Water:	Negligible
Vapor Pressure:	No Data	Specific Gravity:	1.32

#### Section 10 - Stability and Reactivity

.....

**Chemical Stability: Conditions to Avoid (if unstable):**  Stable None

## Copps Industries, Incorporated Mequon, WI 53092-4473 Telephone: (262) 238-1700

Section 10 - Stability and Reactivity (con't.)				
Incompatibility (Materials to Avoid): Hazardous Decomposition Products: Hazardous Polymerization:	Acids, strong oxidizing agents. None Contact with epoxy hardeners under uncontrolled conditions. May release excess heat and vapors.			
	Section 11 - Toxicological Properties			
Acute Oral Toxicity (LD50, RAT):	No data available.			

Acute Oral Toxicity (LD50, RAT): Acute Dermal Toxicity (LD50, RABBIT): Acute Inhalation Toxicity (LC50, RAT):

#### Section 12 - Ecological Information

No data available.

No data available

No data available.

Section 13 - Disposal Considerations

Waste Disposal: This material does not contain any VOC's (volatile organic compounds). Dispose of material in accordance with applicable, local, state, and federal laws and regulations. The state and local regulations and laws may differ from federal regulations, and laws may change or be reinterpreted. This information only applies to the material as manufactured. Processing, use, or contamination may make the information in appropriate, inaccurate, or incomplete. Responsibility for proper waste disposal is with the owner of the waste.

Section 14 - Transport Information					
DOT Non-Bulk Shipping Name:	Resin compound - not regulated	UN#:	Not regulated		
DOT Bulk Shipping Name:	Resin compound - not regulated	Packing Group:	Not regulated		
Technical Shipping Name:	NMFC Item 46030, Class 55	IMO Shipping Data:	Resin compound - not regulated		
DOT Hazard Class:	Not regulated	ICAO/IATA Shipping Data:	Resin compound - not regulated		

Section 15 - Regulatory Information

# US FEDERAL REGULATIONS:

Toxic Substances Control Act (TSCA): All components are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory or are not required to be listed on the TSCA Inventory.

OSHA (29CFR1910.1200) Hazard Class(es): Irritant. Sensitizer

EPCRA Section 312 (40CFR370) Hazard Classes: Immediate Health Hazard. Delayed Health Hazard.

EPCRA Section 313 (40CFR372): Toxic chemicals above "de minimus" level: None

#### STATE REGULATIONS:

California Proposition 65 Substances: (components known to the State of California to cause cancer and/or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Water and Toxic Enforcement Act of 1986"). None

## **INTERNATIONAL REGULATIONS**

Canada: WHMIS Hazard Classification: Class D, division 2B WHMIS Risk Phrases: Eye or skin irritant. Skin sensitizer. WHMIS Symbols: Stylized T

#### Section 16 - Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither Copps Industries nor any of its agents assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

 Revision Date:
 01/13/12

 Replaces Revision Dated:
 01/28/10

**Revised By:** Aleksey Kozlov **Title:** Technical Director

\_\_\_\_\_

\_\_\_\_\_

Page: 1 of 3 (K-501 H) Date Prepared: 01/13/12 Revision Number: 7

	Secti	on 1 - Material Iden	tification			
Product Name:	B-501					
Product Type:	Epoxy Hardener Compound					
Manufacturer:	Copps Industries, Incorporated 10600 N. Industrial Drive Mequon, WI 53092-4473					
Telephone Number:	(262) 238-1700					
Emergency Number (s):	(800) 255-3924 (813) 248-0585	24 hrs. 24 hrs.	(Continental U.S.) (Outside Continental U.S.)			
Revision Notes:	Annual Update					
	Secti	on 2 - Hazardous In	gredients			
$\frac{\#}{1.} \qquad \frac{\text{wt \%}}{>1 \%}$		hemical Name mine				

#### **OSHA & ACGIH EXPOSURE LIMITS**

		TWA		STEL		CEILING	
		ppm	mg/m3	ppm	mg/m3	ppm	mg/m3
1.	OSHA	N/E	N/E	N/E	N/E	N/E	N/E
	ACGIH	N/E	N/E	N/E	N/E	N/E	N/E

*N/E* = *Not Established* 

			Section 3 - Heal	th Hazards	
*****	*****	*****	*****	*********	******
			EMERGENCY (	OVERVIEW	
*****	*****	******	*****	*******	******
HMIS HEALTH RATING	: 3	FLAM	MABILITY: 1	I	REACTIVITY: 0
HMIS Hazard Rating	Least - 0	Slight - 1	Moderate - 2	High - 3	Extreme - 4

A clear liquid with an amine odor. Corrosive to skin. Corrosive to eyes. Severe skin irritant. Severe eye irritant. May cause skin sensitization. May cause respiratory sensitization. Can burn in fire, releasing possible hazardous vapors, gases and fumes. Do not torch or weld on cured epoxy. Hazardous fumes and vapors may be released.

**Routes of Exposure:** Eye Contact, Skin Contact, Inhalation, Ingestion.

Health Hazards: Corrosive to skin. Corrosive to eyes. Severe skin irritant. Severe eye irritant. May cause skin sensitization. May cause respiratory sensitization.

Target Organs: Eyes, Skin, and Respiratory System.

Signs and Symptoms of Exposure (Acute Effects): Burns of the eye may cause blindness. Contact of undiluted products with the eyes or skin quickly causes severe irritation and pain and may cause burns, necrosis, and permanent injury. Inhalation of mists may severely damage contacted tissue and produce scarring. Product is readily absorbed through the skin and may cause discomfort, injury or serious health problems unless treated properly.

Signs and Symptoms of Exposure (Possible Longer Term Effects): This substance may cause respiratory sensitization to exposed workers. Medical Conditions Generally Aggravated by Exposure: Asthma, chronic respiratory disease (e.g. Bronchitis, emphysema). Eye disease, skin disorders and allergies.

Carcinogens under OSHA, ACGIH, NTP, IARC, other: This product contains no carcinogens in concentrations of 0.1 percent or greater.

**Copps Industries, Incorporated** 10600 N. Industrial Drive Mequon, WI 53092-4473 Telephone: (262) 238-1700 \_\_\_\_\_

\_\_\_\_\_

Page: 2 of 3 (K-501 H) Date Prepared: 01/13/12 **Revision Number: 7** 

------

Section 4 - First Aid

pH: Vapor Pressure:	No Data	Specific Gravity: 1.03 Section 10 - Stability and Reactivity
-	No Data	Specific Gravity: 103
nH:	110 Dunu	
Gudi .	No Data	Solubility in Water: Negligible
Odor:	Amine	Melting Point:     > 200 F       Mot applicable
Physical Form: Color:	Liquid Clear	Vapor Density:Heavier than airBoiling Point:> 200 °F
		9 - Typical Physical and Chemical Properties
Hand Protection: Neop Respiratory Protection: areas, or when condition Protective Clothing: In	rene rubber gloves. Cuffed bu Not necessary under most op s cause high vapor concentration pervious clothing. Slickersuit	<ul> <li>goggles. Contact lenses should not be worn while using this product.</li> <li>ityl rubber gloves. Nitrile rubber gloves.</li> <li>berating conditions. NIOSH approved organic vapor respirator should be used in confined ons. If the percent oxygen is below normal then use self-contained breathing apparatus.</li> <li>t. Rubber boots. Full rubber suit (rain gear). Butyl or latex protective clothing.</li> <li>safety showers should be easily accessible.</li> </ul>
		n 8 - Personal Protection/Exposure Controls
Handling: Avoid breath drink, or smoke. Other Precautions: E contaminated clothing ar	Emergency showers and eye nd gear. Decontaminate. Destr	ventilated workspace. Avoid contact with skin, eyes, or clothing. When handling, do not ea wash stations should be readily accessible. Wash thoroughly after handling. Remov roy leather or any articles, which can not be decontaminated.
		Section 7 - Handling and Storage
vacuum truck. Dispose entering sewers or water Other Emergency Advi	of material in accordance with ways. ce: Wear protective clothing, l	a local, state and federal regulations. Wash area with soap and water. Prevent washings from boots, gloves, respirator, and eye protection.
off or remove all ignition	n sources. Construct a dike to p	<b>ces, diking etc.</b> ) Reduce vapor spreading with a water spray. Stop the leak, if possible. She prevent spreading. ver area. Transfer to containers by suction. For large spills, recover spilled material with
		ection 6 - Accidental Release Measures
Extinguishing Media: 1 Special Fire Fighting P and respiratory protection	): > 200 °F (UEL): No data ion (OSHA/NFPA): This proc Foam, Carbon Dioxide (CO2), Procedures: Keep personnel r n (SCBA). Cool fire exposed o osion Hazards: Hazardous co	Lower Explosion Limit (LEL):         No data           Auto Ignition Temperature:         No data           duct is considered neither flammable nor combustible, but will burn if involved in a fire.         or dry chemical.           removed from area and upwind of fire.         Wear full fire-fighting turnout gear (full bunker gear)
		Section 5 - Fire and Explosion Data
Skin Contact: Remove Cover the affected area OINTMENTS. Control Inhalation: Remove vic Ingestion: In the event	contaminated clothing/shoes a with a sterile dressing or cl shock if present. tim to fresh air and provide ox of ingestion, administer 3-4 gla	and wipe excess from skin. Immediately flush affected area with water for at least 15 minutes lean sheeting and seek medical attention immediately. DO NOT APPLY GREASES Of tygen. If breathing is difficult, seek medical attention. asses of milk or water. DO NOT INDUCE VOMITING. Seek medical attention immediately
Eve Contact. Hold evel	ids apart and immediately flus	h eyes with plenty of water for at least 15 minutes. Seek medical attention.

Chemical Stability: Stable

Incompatibility (Materials to Avoid): Acids, strong oxidizing agents.

Conditions to Avoid (if stable): None Hazardous Decomposition Products: None

Hazardous Polymerization: Contact with epoxy resins under uncontrolled conditions. May release excess heat and vapors.

Copps Industries, Inc. 10600 N. Industrial Drive			Dogo, 2 of 2 (V. 501 H)
Mequon, WI 53092-4473		Page: 3 of 3 (K-501 H) Date Prepared: 01/13/12	
Telephone: (262) 238-1700			Revision Number: 7
	Section 11 - Toxicolog	ical Properties	
Acute Oral Toxicity (LD50, RAT):	No data available. BIT): No data available.		
Acute Dermal Toxicity (LD50, RAB			
Acute Inhalation Toxicity (LC50, RA			
	Section 12 - Ecologica		
No Data Available			
	Section 13 - Disposal (	Considerations	
	applies to the material as manufacture Responsibility for proper waste disposa Section 14 - Transpor	al is with the owner of the waste.	tion may make the information in
DOT Non-Bulk Shipping Name:	Caustic Alkali Liquids, N.O.S.	 UN#:	UN1719
DOT Bulk Shipping Name:	Caustic Alkali Liquids, N.O.S.	Packing Group:	III
Technical Shipping Name:	Contains 2 Cycloaliphatic Amines	IMO Shipping Data:	Caustic Alkali Liquid N.O.S.
DOT Hazard Class:	8	ICAO/IATA Shipping Data:	Caustic Alkali Liquid N.O.S.
	Section 15 - Regulator	y Information	
Inventory or are not required to be liste OSHA (29CFR1910.1200) Hazard C EPCRA Section 312 (40CFR370) Ha	-	he EPA Toxic Substances Control I. Delayed Health Hazard.	Act (TSCA) Chemical Substance
	STATE REGULA S: (components known to the State of nder the "Safe Drinking Water and Toxic	California to cause cancer and/or re	

## INTERNATIONAL REGULATIONS

Canada: WHMIS Hazard Classification:	Class D, Division 2A Class D, Division 2B Class E
WHMIS Risk Phrases:	Causes burns. Skin Sensitizer. Lung sensitizer.
WHMIS Symbols:	Stylized T, test tube/hand

Section 16 - Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither Copps Industries nor any of its agents assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

 Revision Date:
 01/13/12

 Replaces Revision Dated:
 01/28/10

**Revised By:** Bill Simek **Title:** Laboratory Manager